



TECHNICAL SPECIFICATIONS, DIMENSIONS

PRODUCT NAME	CODE
Fastfoot® II	FF37, FF50, FF62, FF74
Fastbag® II	FB18, FB24, FB30, FB36

SECTION I – TECHNICAL SPECIFICATIONS				
		<i>Imperial</i>	<i>Metric</i>	<i>Test Method</i>
Color	Natural			
Core diameter	Cardboard	1.5 in	38mm	
Construction	warp	10 tapes/in	3.94 tapes/cm	ASTM D3775
Construction	weft	10 tapes/in	3.94 tapes/cm	ASTM D3775
Coating	LDPE	0.0098 in	250 µm	ASTM D1777
Weight		3.83 oz/yd ²	130 g/m ²	ASTM 5261
Strip tensile	warp	152.8 lbs	680N	ASTM D5035
Strip tensile	weft	132.0 lbs	587N	ASTM D5035
Grab tensile	warp	166.7 lbs.	741.5N	ASTM D5034
Grab tensile	weft	146.1 lbs.	650N	ASTM D5034
Tongue tear	warp	35.0 lbs	156N	ASTM 2262
Tongue tear	weft	35.4 lbs	157N	ASTM 2262
Nominal tear	warp	45.1 lbs	200.6N	ASTM 2262
Nominal tear	weft	41.5 lbs	184.6N	ASTM 2262
Water vapor transmission		0.03906 psi	0.0272 kPa	ASTM E96B
Permeance		0.0628 perms	3.59E-09 g/Pa.s.m ²	ASTM E96B

SECTION II – ROLL, BOX SIZE & WEIGHT				
	<i>FF37 Edging</i>	<i>FF50 Narrow</i>	<i>FF62 Standard</i>	<i>FF74 Wide</i>
<i>Width (in)</i>	37	50	62	74
<i>Length (ft)</i>	100	100	100	100
<i>Weight/roll (lbs)</i>	8.3	11.2	13.9	16.6
<i>Rolls/box</i>	8	4	4	4
<i>Weight/box (lbs)</i>	68	46	57	68
<i>Box height (in)</i>	39	27	33	39
<i>Box length, width (in)</i>	10	10	10	10